

FJM Specification - Indoor Units

FLUX PRO



MSP Duct



- Narrow Width
- Strong and Large Coverage Area
- Silent Operation with the Static Pressure Control
- Easy to Maintain



Pre Filter



Easy Filter



High Lift-up



Smart Control



Wired RC

Model				MH052FUEA
Power Supply		Φ, #, V, Hz		1,2,230-240,50
Mode				HPHR
Performance	Capacity (Nominal)	Cooling	kW	5.20
			Btuh	17,700
	Heating	kW	6.00	
		Btuh	20,500	
Power	Power Input (Nominal)	Cooling	W	170.00
		Heating		170.00
	Current Input (Nominal)	Cooling	A	1.04
		Heating		1.04
Fan	Motor	Type	-	Strocco Fan
		Output	W	124 x 1
	Air Flow Rate	High / Mid / Low (UL)	CMM	16,301/5,001/3,50
			lit	271,67/250,00/225,00
External Static Pressure	Min. / Std. / Max.	mmAq	0,00/4,00/8,00	
		Pa	0,00/39,23/78,45	
Piping Connections	Liquid Pipe		Ø, mm	6,35
			Ø, inch	1/4"
	Gas Pipe		Ø, mm	12,70
			Ø, inch	1/2"
	Drain Pipe		Ø, mm	VP25 (D0 32,JD 25)
Field Wiring	Power Source Wire	Below 20m / Over 20m	mm ²	1,5 - 2,5
	Transmission Cable		mm ²	0,75 - 1,50
Refrigerant	Type		-	R410A
	Control Method		-	EEV NOT INCLUDED
Sound	Sound Pressure	High / Mid / Low	dB(A)	37,0/35,0/33,0
	Sound Power	High / Mid / Low	dB(A)	-
Dimensions	Net Weight		kg	29,00
	Shipping Weight		kg	34,00
	Net Dimensions (WxHxD)		mm	900 x 260 x 480
	Shipping Dimensions (WxHxD)		mm	1146 x 345 x 584
Panel Size	Panel Model		-	-
	Panel Net Weight		kg	-
	Shipping Weight		kg	-
	Net Dimensions (WxHxD)		mm	-
	Shipping Dimensions (WxHxD)		mm	-
Additional Accessories	Drain Pump		-	MDP-M075SGUG
	Max. Lifting Height / Displacement	mm / liter/h	-	-
	Air Filter		-	-

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

Optional Accessories

Individual Controllers



MWR-WE10



MWR-WH00



MWR-SH00



MR-CH00



MFK-A00



MFW-10A

Drain Pump



MDP-M075SGUG

Standard Accessories

Individual Controllers



Individual Controller