

Slim 1Way Cassette



- Slim and Compact Design
- Quiet Operation
- No Overflowing Drain Water



Model		M420PSEA		M430PSEA	
Power Supply	Φ, #, V, Hz	1, 2, 220-240, 50		1, 2, 220-240, 50	
Mode		HP14R		HP14R	
Performance	Capacity (Nominal)	Cooling	Btu/h	2,600	3,500
		Heating	Btu/h	8,900	11,900
Power	Power Input (Nominal)	Cooling	W	2,900	3,900
		Heating	W	9,900	13,000
Fan	Current Input (Nominal)	Cooling	A	45.00	50.00
		Heating	A	45.00	50.00
Fan	Motor	Type	-	Crossflow Fan	Crossflow Fan
	Air Flow Rate	Output	W	80 x 1	80 x 1
Fan	External Static Pressure	Min / Std / Max	mmAq	6,200 x 204 x 20	7,600 x 600 x 60
			Pa	103.3386/67770.00	126.67110/00993.33
Piping Connections	Liquid Pipe	Ø, mm	-	-	-
		Ø, inch	6.35	6.35	6.35
Piping Connections	Gas Pipe	Ø, mm	1/4"	1/4"	1/4"
		Ø, inch	9.52	9.52	9.52
Field Wiring	Drain Pipe	Ø, mm	3/8"	3/8"	3/8"
		Ø, inch	VP00 (OD 26, ID 20)	VP00 (OD 26, ID 20)	VP00 (OD 26, ID 20)
Field Wiring	Power Source Wire	Below 20m / Over 20m	mm ²	1.5 - 2.5	1.5 - 2.5
	Transmission Cable		mm ²	0.75 - 1.50	0.75 - 1.50
Refrigerant	Type		R410A	R410A	R410A
	Control Method		-	EEV NOT INCLUDED	EEV NOT INCLUDED
Sound	Sound Pressure	High / Mid / Low	dBA	30.008/0.025.0	32.000/0.027.0
	Sound Power	High / Mid / Low	dBA	-	-
Dimensions	Net Weight		kg	11.00	11.00
	Shipping Weight		kg	14.00	14.00
Panel Size	Net Dimensions (WxHxD)		mm	970 x 135 x 410	970 x 135 x 410
	Shipping Dimensions (WxHxD)		mm	1164 x 212 x 478	1164 x 212 x 478
Additional Accessories	Panel Model		-	PSSMA	PSSMA
	Panel Net Weight		kg	3.10	3.10
Additional Accessories	Shipping Weight		kg	4.50	4.50
	Net Dimensions (WxHxD)		mm	1180 x 225 x 480	1180 x 225 x 480
Additional Accessories	Shipping Dimensions (WxHxD)		mm	1259 x 144 x 539	1259 x 144 x 539
	Drain Pump		-	-	-
Additional Accessories	Max. Lifting Height / Displacement	mm / liter/h	-	-	-
	Air Filter		-	-	-

* Product Specifications in the Publication can be changed without a prior notice. Because there is always an ongoing improvement on our product.

Optional Accessories

